


Single Row Ball Slewing Ring

With External Gear



With External Gear

Bearing Model	Dimensions			Mounting Dimensions						Structural Dimension					Gear data					weight (kg)
	Dmm	dmm	Hmm	D1mm	D2mm	n	omm	dmmm	Lmm	n1	D3mm	d1mm	H1mm	hmm	bmm	x	Mmm	Demm	z	
011.45.1400	1540	1260	110	1487	1313	40	26	M24	48	5	1402	1398	100	10	90	0.5	12	1605.6	131	480
012.45.1400																	14	1607.2	112	
011.35.1400	1540	1260	110	1487	1313	40	26	M24	48	5	1401	1398	100	10	90	0.5	12	1605.6	131	480
012.35.1400																	14	1607.2	112	
011.45.1600	1740	1460	110	1687	1513	45	26	M24	48	5	1602	1598	100	10	90	0.5	14	1817.2	127	550
012.45.1600																	16	1820.8	111	
011.35.1600	1740	1460	110	1687	1513	45	26	M24	48	5	1601	1598	100	10	90	0.5	14	1817.2	127	550
012.35.1600																	16	1820.8	111	
011.45.1800	1940	1660	110	1887	1713	45	26	M24	48	5	1802	1798	100	10	90	0.5	14	2013.2	141	610
012.45.1800																	16	2012.8	123	
011.35.1800	1940	1660	110	1887	1713	45	26	M24	48	5	1801	1798	100	10	90	0.5	14	2013.2	141	610
012.35.1800																	16	2012.8	123	
011.60.2000	2178	1825	144	2110	1891	48	33	M30	60	8	2002	1998	132	12	120	0.5	16	2268.8	139	1100
012.60.2000																	18	2264.4	123	
011.40.2000	2178	1825	144	2110	1891	48	33	M30	60	8	2001	1998	132	12	120	0.5	16	2268.8	139	1100
012.40.2000																	18	2264.4	123	
011.60.2240	2418	2065	144	2350	2131	48	33	M30	60	8	2242	2238	132	12	120	0.5	16	2492.8	153	1250
012.60.2240																	18	2498.4	136	
011.40.2240	2418	2065	144	2350	2131	48	33	M30	60	8	2241	2238	132	12	120	0.5	16	2492.8	153	1250
012.40.2240																	18	2498.4	136	
011.60.2500	2678	2325	144	2610	2391	56	33	M30	60	8	2502	2498	132	12	120	0.5	18	2768.4	151	1400
012.60.2500																	20	2776	136	
011.40.2500	2678	2325	144	2610	2391	56	33	M30	60	8	2501	2498	132	12	120	0.5	18	2768.4	151	1400
012.40.2500																	20	2776	136	
011.60.2800	2978	2625	144	2910	2691	56	33	M30	60	8	2802	2798	132	12	120	0.5	18	3074.4	168	1600
012.60.2800																	20	3076	151	
011.40.2800	2978	2625	144	2910	2691	56	33	M30	60	8	2802	2798	132	12	120	0.5	18	3074.4	168	1600
012.40.2800																	20	3076	151	
011.75.3150	3376	2922	174	3286	3014	56	45	M42	84	8	3152	3147	162	12	150	0.5	20	3476	171	2800
012.75.3150																	22	3471.6	155	
011.50.3150	3376	2922	174	3286	3014	56	45	M42	84	8	3152	3147	162	12	150	0.5	20	3476	171	2800
012.50.3150																	22	3471.6	155	
011.75.3550	3776	3322	174	3686	3014	56	45	M42	84	8	3552	3547	162	12	150	0.5	20	3876	191	3500
012.75.3550																	22	3889.6	174	
011.50.3550	3776	3322	174	3686	3014	56	45	M42	84	10	3552	3548	162	12	150	0.5	20	3876	191	3500
012.50.3550																	22	3889.6	174	
011.75.4000	4226	3772	174	4136	3864	60	45	M42	84	10	4002	3997	162	12	150	0.5	22	4329.6	194	4200
012.75.4000																	25	4345	171	
011.50.4000	4226	3772	174	4136	3864	60	45	M42	84	10	4002	3998	162	12	150	0.5	22	4329.6	194	4200
012.50.4000																	25	4345	171	
011.75.4500	4726	4272	174	4636	4364	60	45	M42	84	10	4502	4497	162	12	150	0.5	22	4835.6	217	5100
012.75.4500																	25	4845	191	
011.50.4500	4726	4272	174	4636	4364	60	45	M42	84	10	4502	4498	162	12	150	0.5	22	4835.6	217	5100
012.50.4500																	25	4845	191	